


Model: KVM-1708COMBO-DR
1U Rackmount Dual Rail 17" TFT LCD, with 8 port KVM switch



Main Feature

- LCD Monitor & Keyboard could pull-out & push back independently
- One PS/2 console controls up to 16 directly connected computers
- Support an optional remote console (Cat5 based or Over-IP)
- CAT5 console up to 1000 feet away from KVM switch with superior auto-adjust RGB gain/delay control capability

- Support multiple form - PS/2 and USB computers (SUN and MAC)
- Support DOS, Windows, Netware, Unix, Linux, Mac OS
- Hot Pluggable - Add or remove connected PCs without having to power down the KVM switch or PCs.
- Superior video quality - Up To 1280 x 1024, DDC2B (Display Data Channel Standard, Level 2B)
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)
- Support Daisy Chaining up to 7 additional units
- Auto Scan Mode for monitoring PCs
- Firmware upgradeable for staying compatible with new coming computers
- Metal case, rack mountable Support DDC2B for all ports
- Built-in AUTO self-locking & releasing mechanism system at end position (safety feature)

Specification		
Product Model		KVM-1708COMBO-DR
LCD	Size	17" TFT
	Resolution	1280 X 1024
	Max. color	16.7M
	Luminance	300 cd/m2
	View Angel	178°(H) , 178°(V)
	Pixel Pitch	0.264 x 0.264 mm
	Contrast Ratio	1000 : 1
Computer Connections	Direct	8
	Maximum	128
Computer Port Selection		OSD , Hot Key , Push Button
Connector	Power	AC Inlet
	Computer	HDB 15 Female
	Daisy Chain	HDB 15 Female
	Console Port	Plus one Optional Modules: Selectable CAT5-Based or IP-Based Remote Console
CAT5-Based Remote Transmit / Receive Module (KDCC-300T/KDCC-300R)		RJ-45 Connector CAT5 console up to 1000 feet away from KVM switch with superior auto-adjust RGB gain/delay control capability
IP-Based Remote Console Module (KDIP-101)		RJ-45 8P8C for 10/100M Ethernet DB-9 pin male for Modem, Null modem and serial power Control Mini USB 2.0 receptacle
LEDs	Port	8
	Power	1
Button / Switch	Power Switch	Rock Switch
	LCD Adjustment	Button
Hotkey		Provide various Hotkey (Scroll-Lock/ Cap-Lock/ Num-Lock/ Alt/ Ctrl/ Win)
Auto-Scan Intervals		5 ~ 99 Sec.
Keyboard / mouse Emulation		PS/2
Video Resolution (Local Console)		1280 x 1024
Video Resolution (Remote Console)		1600 x 1200 for CAT5-Based 500 feet remote console, 1024 x 768 for CAT5-Based 1000 feet remote console, 1600 x 1200 for IP-Based remote console

Power Input Rating		100-240VAC ; 50/60Hz ; 1A
Power Consumption		37W
Environment	Operating Temperature	0-50°C
	Store Temperature	-20-60°C
	Humidity	0-80% RH , NC
Housing		Heavy Duty Steel
Size		19" Rack mount, 1U
Net / Gross Weight		23 / 27 kg
Dimensions (W*D*H)		482 x 700 x 44 mm
Certificated		CE/FCC
Order Information		
KVM-1708COMBO-DR		1U Rackmount Dual Rail 17" TFT LCD, with 8 port KVM switch
KCVU-018 (optional)		USB, 2 in 1 KVM Cable , 1.8 meter length
KCVU-030 (optional)		USB, 2 in 1 KVM Cable , 3.0 meter length
KCVU-050 (optional)		USB, 2 in 1 KVM Cable , 5.0 meter length
KCVU-018 (optional)		PS/2, 3 in 1 KVM Cable , 1.8 meter length
KCVU-030 (optional)		PS/2, 3 in 1 KVM Cable , 3.0 meter length
KCVU-050 (optional)		PS/2, 3 in 1 KVM Cable , 5.0 meter length
KDDC-300T & KDDC-300R (optional)		CAT5-Based Remote Transmit & Receive Module - for 300 meter
KDIP-101 (optional)		IP-Based Remote Console Module

Structure Diagram Unit :mm

