

Model: NWS-4000T
8U 19'' Rack Mount Workstation, with 15'' TFT LCD, with Touch Screen



Main Feature

- Compact 8U high Rack Mount Workstation
- Front 15' TFT LCD display
- Aluminum front panel and Steel chassis, Front Panel meet IP65/NEMA4 Standard
- Front panel Built in OSD, Membrane keypad, Touch pad
- Front Accessible USB x 1, 5.25' CD-ROM x 1, 3.5' FDD x 1
- Flexible mechanical design support STD PS2 supply
- Support 10-Slots Backplane or 9.6"x9.6" Micro ATX MB

Specification

- Front panel: Aluminum, meet NEMA4/IP65
- LCD display: VGA Interface
 - Display Type : 15" XGA TFT LCD
 - Max.color : 16.2M
 - View Angle : 150° (H) , 135° (V)
 - Contrast Ratio : 700 : 1
 - Power Consumption : 11.27W
 - Resolution : 1024x768
 - Luminance : 250 cd/m2
 - Pixel Pitch : 0.297 x 0.297 mm
 - Response Time : 8 ms
 - LCD MTBF : 50,000hrs
- Display setting: OSD On front panel

- Touch Screen
 - Type: Analog resistive type : 25VDC \geq 20M Ω
 - Light transmission: 80% or more
 - Power consumption: <5V @1mA
 - Operating force : \leq 100g
 - Resolution: continuous
 - Controller: RS-232 interface(or USB option)
 - Surface hardness : 3H
 - Life expectancy : 1 Million
- Disk Driver Bay: Supports 5.25' CD-ROM x 1, 3.5' FDD x 1(External), 3.5' HDD x 1(Internal)
- Cooling system: One 120 x 120 x 25mm Cooling fan with air filter (Right side)
One 92x92x25mm Cooling fan as optional (Backside)
- Membrane Keypads:60 Operating keys,12 function keys
- Keyboard:6-Pin PS2 keyboard connector with dust protection door on front panel
- Touch pad: PS2 Mouse
- Indicators: LEDS for power on/off and HDD activity
- Touch screen: Resistive Type with RS-232 controller (optional)
- Dimension(W x H x D):483*355* 255.3mm
- Packing Dimension: 600x370x 510mm
- NET weight: 19.5KG
- Gross weight: 21.2KG

Structure Diagram

