

Model: CL-1716COMBO-L
1U Rackmount 17" TFT LCD with Eight port KVM switch & Local Console



Main Feature

16 pcs. Of 1.8 meter KVM COMBO cable

- One console controls 16 connected computers
- A-Grade 17'' LED-backlit LCD Full HD panel
- LCD module rotates up to 120 degrees for a more comfortable viewing angle
- Front USB port for additional Keyboard and Mouse connection
- Additional local console at Rear 2 x USB for KB/Mouse, 1 x VGA for monitor
- Supporting DOS, Windows, Netware, Unix, Linux, Mac OS
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)
- Auto Scan Mode for monitoring PCs
- 1U 19'' rack mountable design, metal case - Integrated full size keyboard and touchpad
- Easy for operate, allow smoothly pulling with self-locking at end position
- Customized Keyboard Language support upon request

Specification		
Product Model		CL-1716COMBO-L
LCD	Size	A-Grade 17'' LED-backlit LCD panel (Ratio: 4:3)
	Resolution	1280 x 1024 @ 60Hz
	Max. color	16.7M
	Luminance	250 cd/m2
	View Angle	140° (H), 130° (V)
	Pixel Pitch	0.264 x 0.297 mm
	Contrast Ratio	1000 : 1
	LCD MTBF	50,000 hours
Computer Connections	Direct / Maximum	16 / 256
Computer Port Selection		OSD, Hot Key, Push Button

Connector	Power	12 VDC Input
	Computer	HDB-15 VGA, USB for Keyboard & Mouse
	USB/VGA - Console port	KB & Mouse (1@Front & 2@Rear) / Monitor
CAT5-Based Remote Transmit / Receive Module (Optional: KV-300)		KVM Extender transmits KVM up to 300m away from a computer using Cat5/5e/6 cable
IP-Based Remote Module (Optional: KCL-101)		IP access to manage KVM & Computers globally
LEDs	Port	16
	Power	1
Button / Switch	Power Switch	Button
	LCD Adjustment	Button
Hotkey		Provide various Hotkey (Scroll/Shift/ Alt/ Ctrl + Num)
Auto-Scan Intervals		3 ~ 60 Seconds
Power Rating (AC to 12VDC/4A adapter)		100-240VAC, 50/60Hz
Environment	Operating Temperature	-10 - 50°C
	Store Temperature	-20 - 60°C
	Humidity	0-80% RH, NC
Housing		Heavy Duty Steel
Size		1U, 19" Rack mount
Rack Installation Depth (front rails to rear rails)		556 - 900mm (Minimum to Maximum adjustable)
Net / Gross Weight		17 / 20KG
Dimensions (W*D*H)		443 x 556 x 45 mm
Certificated		CE/FCC
Ordering Information		
CL-1716COMBO-L	1U Rackmount 17" LCD with 16 port KVM switch local console port, 16 x 1.8 meter KVM Cable	
CL-030PU (Optional)	4 in 1 KVM Cable, USB & PS2 interface, 3 meter length	
CL-050PU (Optional)	4 in 1 KVM Cable, USB & PS2 interface, 5 meter length	
KV-300 (Optional)	KVM Extender transmits up to 300m	
KCL-101 (Optional)	IP-Based Remote Console Module	

Structure Diagram (mm)

