

Model: EIPC-i5-19CT
19" Capacitive Multi Touch Panel PC, with Intel Core i5 processor - 6 x COM; IP65 front protection; Optional WIFI

Main Feature

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- 19" SXGA LED Panel support 1280x1024 pixels
- Intel® Core™ i5 6200U Processor
- Rugged construction design
- Front 6mm Aluminum bezel - NEMA4 / IP 65 compliant
- 6 x RS232 Serial port
- Wide Range 9-36VDC input
- Front flat glass (7H Hardness) with projected capacitive Multi Touch Screen
- (Optional - WIFI) MINI PCI-E WIFI Module with Antenna
- Panel (Flush) mounting with clip
- Meet standard VESA hole (75 & 100 mm), support desk top stand / wall mount / swing arm mounting
- **Application:** Kiosk; Digital Signage; Factory Automation; Processor Automation; Marine / Offshore Industrial ...



Specification	
Product Model	EIPC-i5-19CT
Processor	Intel® Core™ i5 6200U Processor (Dual Core, 2.3 to 2.8GHz, 3M Cache)
Chipset	Intel® SOC integrated
Memory	2 x DDR4L SO-DIMM Socket up to 32GB
Storage	1 x 2.5" SSD/HDD drive bay, 1 x M.2 Slot for SSD
Display	Display Type : 19" SXGA <u>LED Panel</u> LCD Resolution : 1280 x 1024 Luminance : 250 cd/m2 View Angel : 170°(H), 160°(V)
Audio	Realtek ALC662 HD Audio Controller
LAN	Realtek RTL8111F Gigabit LAN
USB port	2 x USB 3.0 & 4 x USB 2.0
Graphic	Intel® HD Graphics 520, VGA (Max. resolution @ 1920 x 1200) + HDMI 1.4 (supporting a maximum resolution of 4096 x 2304@24Hz)
Expansive interface	1 x Mini PCI-E 2.0

Back panel I/O port	1 x RJ45, 2 x USB 3.0, 4 x USB 2.0, 1 x VGA,; 1 x HDMI, 1 x Lin-in / Lin-out, 6 x COM 1 x HDD/PWR LED, 1 x Power / Reset Switch, 1 x PWR-In 3 PIN Terminal Block
Supporting OS	Windows 7/8.1/10, Linux
Touch Screen	Internal USB interface controller - Projected Capacitive Multi Touch (10 points) Light transmission: 85% or more Surface hardness : 7H
Wireless LAN (optional)	MINI PCI-E WIFI Module with Antenna
Power Supply	9-36VDC input with 3 pin termination block
Construction	Heavy duty steel and aluminum front panel
Environment	Operating temperature: 0°C to 60°C Relative humidity: 10% to 90%non-condensing Vibration: 17 to 500HZ 1G PTP, Shock: 1G /peak(11m sec)
Compliance	CE; FCC; ROHS
Dimension W x H x D (mm)	456 x 371 x 72
Ordering Information:	
EIPC-i5-19CT	19" Capacitive Multi Touch Panel PC - Intel Core i5, with 100-240VAC to DC 12V/5A adapter
<u>Optional - RAM</u>	4 to 32GB DDR4L SO-DIMM
<u>Optional - SSD / HDD</u>	64 GB to 2TB 2.5'' SSD, 500GB to 2TB 2.5'' SATA HDD
<u>Optional - WIFI</u>	MINI PCI-E WIFI Module with Antenna
<u>Optional - OS</u>	Windows 7/ 8.1 / 10, Linux

Structure Diagram (Panel cut-off dimension: 446 x 361mm)

