

Model: EPC-3855U-4COM
Industrial Embedded Computer - Intel Celeron 3855U (Skylake-U), with 4 x COM



- With VGA + HDMI 1.4 (Supports Ultra HD / 4K resolution), GLAN, Audio; 4 x RS232, 5 x USB
- Ultra Low Power Consumption processor - 15watt
- BIOS Set-up "Auto Power-On" and "Wake on LAN"
- **Application:** Digital Signage, Factory Automation; Processor Automation; Intelligent Traffic Control; Medical Equipment; Marine / Offshore Industrial...

Specification	
Item	Description
Processor	Intel® Celeron 3855U Processor (Dual Core, 1.6GHz, 2M Cache)
Chipset	Intel® integrated with processor
Memory	1 x DDR3L SO-DIMM Socket up to 8GB
Storage	Space for 1x 2.5" bay for HDD/SSD
Graphic	Intel® HD Graphics 510, VGA (Max. resolution @ 1920 x 1200) + HDMI 1.4 (supporting a maximum resolution of 4096 x 2304@24Hz)
Storage	Space for 2 x 2.5" HDD/SSD, 2 x SATA III port & 1 x M.2
Audio	Realtek ALC662 HD Audio Controller
LAN	Realtek RTL8111F Gigabit LAN

USB port	2 x USB 3.0 and 3 x USB 2.0
Expansive interface	1 x Mini PCI-E 2.0, 1 x M.2 Slot for SSD
I/O port	1 x HDMI; 1 x VGA; 1 x RJ45; 3 x USB 2.0; 2 x USB 3.0; 4 x RS232; 1 x Lin-in/ Lin-out; 1 x Power Switch; 1 x DC input
Power Supply	Input: 100~240VAC, 50/60Hz; Output: DC 12V/ 5A adapter
Construction	Aluminum Case with VESA mounting bracket
OS supporting	DOS; Windows 7/8.1/10; Linux
Environment	Operating temperature: -10 °C to 60 °C Storage temperature: -20 °C to 80 °C Storage humidity: 10% to 90% non-condensing Vibration: 17 to 500HZ 1G PTP; Shock: 1G /peak(11m sec)
Dimension W x H x D (mm)	200 x 200 x 50