

Model: KVM-1701COMBO-S
1U Rackmount 17" TFT LCD ,with 1 port KVM switch (Short Depth)



Main Feature

- 1 PS/2 console controls 1/8/16 directly connected computers
- 86 keys keyboard with touch pad
- Cascade switches up to 8 levels and Mix switches between Cat5 & DB-15 KVM
- Support DOS, Windows, Netware, Unix, Linux, Mac OS
- Hot Pluggable - Add or remove connected PCs without having to power down the KVM switch/PCs
- Superior video quality - Up To 1024X768, DDC2B
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)
- Auto Scan Mode for monitoring PCs
- Firmware upgradeable for staying compatible with new coming computers
- Metal case, rack mountable Support DDC2B for all ports

Specification		
Product Model		KVM-1701COMBO-S
LCD	Size	17" TFT
	Resolution	1280 x 1024
	Max.color	16.7 M
	Luminance	300 cd/m2
	View Angle	178° (H) , 178° (V)
	Pixel Pitch	0.264 x 0.264 (mm)
	Contrast Ratio	1000 : 1
LEDs / Port		1
Power		1
Computer Connections		1
Maximum Computer Connections		225
Computer Connectors		2 x PS2, 1 x USB, 1 x VGA
Daisy Chaining		Daisy Chainable up to 8 levels ; Connector : DB-15 (female type)

Computer Selection		On Screen Display (OSD) , Hot Key , Push Button
Hotkey		Provide various Hotkey (Scroll-Lock/ Cap-Lock / Num-Lock / Alt-Ctrl-Win)
Auto-Scan Intervals		5 - 99 Sec.
Keyboard / mouse Emulation		PS/2
Power Adapter		AC 100-240V , 50/60Hz , DC 12V / 4A , 48Watt
Housing		Metal
Size		19" Rack mount, 1U
Environment	Operating Temperature	0 - 50 °C
	Store Temperature	-20 -60 °C
	Humidity	10% to 90%,non-condensing
Physical Dimensions (W x H x D)		482.6 x 43.6 x 457.2 mm
Packing Dimensions (W x H x D)		605 x 168 x 700 mm
Certificated		CE/FCC
Ordering Information		
KVM-1701COMBO-S		1U Rackmount 17" TFT LCD ,with 1 port KVM switch (Short Depth)
KCVU-018 (optional)		USB, 2 in 1 KVM Cable , 1.8 meter length
KCVU-030 (optional)		USB, 2 in 1 KVM Cable , 3.0 meter length
KCVU-050 (optional)		USB, 2 in 1 KVM Cable , 5.0 meter length
KCVP-018 (optional)		PS/2, 3 in 1 KVM Cable , 1.8 meter length
KCVP-030 (optional)		PS/2, 3 in 1 KVM Cable , 3.0 meter length
KCVP-050 (optional)		PS/2, 3 in 1 KVM Cable , 5.0 meter length

Structure Diagram

Unit :mm

