

Model: KVM-1908COMBO-DR
1U Rackmount Dual Rail 19" TFT LCD, with 8 port KVM switch



Main Feature

- LCD Monitor & Keyboard could pull-out & push back independently
- One PS/2 console controls up to 16 directly connected computers
- Support an optional remote console (Cat5 based or Over-IP)
- CAT5 console up to 1000 feet away from KVM switch with superior auto-adjust RGB gain/delay control capability
- Support multiple form - PS/2 and USB computers (SUN and MAC)
- Support DOS, Windows, Netware, Unix, Linux, Mac OS
- Hot Pluggable - Add or remove connected PCs without having to power down the KVM switch or PCs.
- Superior video quality - Up To 1280X1024, DDC2B (Display Data Channel Standard, Level 2B)
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)

- Support Daisy Chaining up to 7 additional units
- Auto Scan Mode for monitoring PCs
- Firmware upgradeable for staying compatible with new coming computers
- Metal case, rack mountable Support DDC2B for all ports
- Built-in AUTO self-locking & releasing mechanism system at end position (safety feature)

Specification		
Product Model		KVM-1908COMBO-DR
LCD	Size	19" TFT
	Resolution	1280 X 1024
	Max. color	16.7M
	Luminance	300 cd/m2
	View Angel	178° (H) , 178° (V)
	Pixel Pitch	0.294 x 0.294 mm
	Contrast Ratio	1000 : 1
Computer Connections	Direct	8
	Maximum	128
Computer Port Selection		OSD, Hot Key, Push Button
Connector	Power	AC Inlet
	Computer	HDB 15 Female
	Daisy Chain	HDB 15 Female
	Console Port	Plus one Optional Modules: Selectable CAT5-Based or IP-Based Remote Console
CAT5-Based Remote Transmit / Receive Module (KDCC-300T/KDCC-300R)		RJ-45 Connector CAT5 console up to 1000 feet away from KVM switch with superior auto-adjust RGB gain/delay control capability
IP-Based Remote Console Module (KDIP-101)		RJ-45 8P8C for 10/100M Ethernet DB-9 pin male for Modem, Null modem and serial power Control Mini USB 2.0 receptacle
LEDs	Port	8
	Power	1
Button / Switch	Power Switch	Rock Switch
	LCD Adjustment	Button
Hotkey		Provide various Hotkey (Scroll-Lock/ Cap-Lock/ Num-Lock/ Alt/ Ctrl/ Win)
Auto-Scan Intervals		5 - 99 Sec.
Keyboard / mouse Emulation		PS/2
Video Resolution (Local Console)		1280 x 1024
Video Resolution (Remote Console)		1600 x 1200 for CAT5-Based 500 feet remote console, 1024 x 768 for CAT5-Based 1000 feet remote console, 1600 x 1200 for IP-Based remote console
Power Input Rating		100-240VAC ; 50/60Hz ; 1A
Power Consumption		37W
Environment	Operating Temperature	0-50°C
	Store Temperature	-20-60°C
	Humidity	0-80% RH , NC

Housing	Heavy Duty Steel
Size	19" Rack mount, 1U
Net / Gross Weight	23 / 27 kg
Dimensions (W*D*H)	482 x 700 x 44 mm
Certificated	CE/FCC
Order Information	
KVM-1908COMBO-DR	1U Rackmount Dual Rail 19" TFT LCD, with 8 port KVM switch
KCVU-018	USB, 2 in 1 KVM Cable , 1.8 meter length
KCVU-030	USB, 2 in 1 KVM Cable , 3.0 meter length
KCVU-050	USB, 2 in 1 KVM Cable , 5.0 meter length
KCVP-018	PS/2, 3 in 1 KVM Cable , 1.8 meter length
KCVP-030	PS/2, 3 in 1 KVM Cable , 3.0 meter length
KCVP-050	PS/2, 3 in 1 KVM Cable , 5.0 meter length
KDDC-300T & KDDC-300R	CAT5-Based Remote Transmit & Receive Module - for 300 meter
KDIP-101	IP-Based Remote Console Module

Structure Diagram Unit :mm

