

Model: PVM-96HB-BNC
8.4" IP67 Sunlight Readable Marine Monitor with BNC input



Main Feature

- 8.4" High Brightness LED Panel support 800 x 600 pixels - Sunlight Readable
- 6mm Aluminum front bezel with strengthen glass
- IP 67 compliant front panel with Anti - Glare glass
- Rugged construction design
- Signals Input: VGA + HDMI + BNC
- OSD control keys to optimize the display (with 0-100% Dimming Control)
- Panel mounting with clip
- Meet standard VESA hole (75 x 75 mm), support desktop stand/wall mount /swing arm mounting
- Shock & Vibration - compliance with EN50155 / MIL-STD-810F / IEC-60945

Specification	
Product Model	PVM-96HB-BNC
LCD Panel	Display Type : 8.4" LED Backlight Resolution : 800 x 600 Max. color : 262K Luminance : 1,000 cd/m2 View Angel : 140° (H), 120° (V) Pixel Pitch : 0.0675 x 0.2025 mm Contrast Ratio : 500 : 1 Response Time : 6 ms MTBF : 30,000hrs
Signal Input / Output	VGA + HDMI + BNC
Protect Glass	3 mm strengthen glass
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and recall

Touch Screen (optional)	Internal USB - Resistive Touch <u>or</u> Projected Capacitive Multi Touch Light transmission: 85% or more Surface hardness : 6H Operation system : DOS; Windows XP / 7 / 10/11; Linux
Power Supply	Input: 12V/5A DC with 110-240VAC Wide range Adapter
Construction	Heavy duty steel and aluminum front panel
Environment	Operating temperature: -10 °C to 55 °C Storage temperature: -20 °C to 70 °C Storage humidity: 10% to 95%, non-condensing Vibration: compliance with MIL-STD-810 Shock: compliance with MIL-STD-810
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	243 x 229 x 47mm

Ordering Information

PVM-96HB-BNC	8.4" IP67 Sunlight Readable Marine Monitor with BNC input
--------------	---

Structure Diagram Unit:mm

