

Model: RMM-7X2
3U, Dual 7" TFT LCD Rack Mount Monitor



Specification	
Product Model	RMM-7X2
LCD Panel	Display Type : 7" VGA TFT LCD Resolution : 800×480 Max. color : 262K Luminance : 350 cd/m2 View Angel (L/R ,U/D): 50/50, 50/50 Pixel Pitch : 0.1905 x 0.1905 mm Contrast Ratio : 200 : 1 Response Time : 30 ms Power Consumption : 4W LCD MTBF : 50,000hrs
Signal Input	VGA , Video, S-Video
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
Power Supply	DC12V@ 4A /48W ,external ac adapter
Construction	Heavy duty steel
Environment	Operating temperature: 32 °F~113 °F (0 °C to 45 °C) Storage temperature: -4 °F~140 °F (-20 °C to 60 °C) Storage humidity: 10% to 95%@ 40°C , on-condensing Vibration: 10 ~ 150Hz, 0.15mm 10 cycles 1G Shock: 30G peak acceleration (11 msec. duration)
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	Dimensions: 482.6*133* 62.7mm Packing Dimension: 600x190x 320mm
Weight	NET weight: 5.7KG Gross weight: 6.7KG

Structure Diagram Unit :mm

