

Model: RPC-100-4VP3-250
1U 19'' Rackmount Chassis with 3 X PCI backplane and 250 watt PSU



Main Feature

- 19-inch rack mountable chassis which meets the EIA RS-310C standard
- Space-saving 1U steel chassis suitable for CT and Firewall/networking field
- Passive backplane with choice of 4 slot butterfly or 3 PCI slots.
- Standard 250-watt AC ATX power supply
- Easily maintainable disk drive bays that allow mounting of Slim DVD & 3.5" disk drives
- Lockable up-cover for protecting original hardware change
- Special modular design allows users to maintain system with minimum down time
- Power-on switch with indicator and independent reset switch
- Power, Hard disk, LED indicators

Specifications

- Physical Dimension (W× D× H): 430mm × 430mm × 44 mm
- Weight: 7kg
- Construction: Heavy-duty steel
- Cooling Fan: 1x(40x40x20mm); 2x(40x40x10mm)
- Disk Drive Bay: Slim DVD & 3.5" disk drives
- Display Indicator : One built-in power LED indicator; One HDD LED indicator
- 2 X Front USB
- Switch: Power On/Off Switch; Reset Switch
- MTBF: 100,000 hrs
- Power Safety: UL, CSA and TUV approved
- EMI: FCC Class A and CISPR 22 approved
- Operating Temp: 0° ~45° C (32° ~113°)
- Storage Temp: 0° ~75° C (32° ~167°)
- Operating Humidity: 5% ~ 95%, Non-condensing
- Storage Humidity: 5% ~ 95%
- Altitude: 10,000 ft (3,000 m)
- Vibration (operating): 1.5G Max
- Shock: 15G peak acceleration (10 msec duration)

Power Supply

- 250Watt AC ATX power supply

Passive Backplane

- CBP-4VP3 (3 x PCI Slots)

Ordering Information

RPC-100-4VP3-250W	1U 19'' Rackmount Chassis with 3 X PCI backplane and 250 watt ATX Power Supply Unit
-------------------	---

Structure Diagram

