

Model: SLR-07T
7" Sunlight Readable Industrial Display with PCT Touch



Main Feature

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- 7" WVGA LED panel support 800x480 pixels
- Front 4mm Aluminum bezel with NEMA4 / IP 65 compliance
- Front flat glass (6H Hardness) with projected capacitive Multi Touch Screen
- Supports 10 points multi-touch via USB interface in Windows 7/8.1/10/11 ...
- Slim design for Panel mount easy installation
- Input signal : VGA + HDMI + AV(BNC) + Audio + USB
- AC 100-240V wide range external AC adapter (with Wide Range 12-24VDC input)

Application

CCTV Monitoring; Kiosk; Digital Signage; Factory Automation; Processor Automation; Marine / Offshore Industrial ...

Specification	
Product Model	SLR-07T
LCD Panel	Display Type : 7" WVGA <u>LED Panel</u> Resolution : 800 x 480 Luminance : 1,000 nit View Angel : 140°(H), 120°(V) Contrast Ratio : 1,000 : 1 LED backlight lifecycle : 50,000hrs
Signal Input	VGA + HDMI + AV (BNC) + Audio + USB
OSD	Auto; Menu; Left; Right; Exit/Select; Power On/Off
Touch Screen	Internal USB interface controller - Projected Capacitive Multi Touch (10 points) Light transmission: 85% or more Surface hardness : 6H Operation system : DOS; Windows XP / 7 / 8.1 / 10 / 11; Linux
Power Supply	Input: 12-24VDC Wide-range

	AC power to DC Adapter: 100-240VAC, 50/60Hz to DC12V/2A
Construction	Aluminum magnesium alloy front panel with heavy-duty steel chassis
Environment	Operating temperature: -20 °C to 60 °C Storage temperature: -30 °C to 70 °C Storage humidity: 10% to 95%, non-condensing Vibration: 50 to 500HZ 1G PTP Shock: 10G /peak(11m sec)
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	210 x 131 x 34
Ordering Information	
SLR-07T	7" Sunlight Readable Industrial Display with PCT Touch

Structure Diagram (Mounting Hole Size: 197 x 119 mm)

