

Model: SLR-121T  
 12.1" Sunlight Readable Industrial Display with PCT Touch



### Main Feature

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- 12" XGA LED panel support 1024x768 pixels
- Heavy-duty PVC with Rugged construction design
- Front flat glass (6H Hardness) with projected capacitive Multi Touch Screen
- Supports 10 points multi-touch via USB interface in Windows 7/8.1/10/11 ...
- Input signal : VGA + HDMI + AV (BNC) + Audio + USB
- AC 100-240V wide range external AC adapter (with Wide Range 12-24VDC input)
- Meet standard VESA hole (75x75mm), support desktop stand/wall mount /swing arm mounting

### Application

Kiosk; Digital Signage; Factory Automation; Processor Automation; Marine / Offshore Industrial ...

Specification	
Product Model	SLR-121T
LCD Panel	Display Type : 12.1" XGA <u>LED Panel</u> Resolution : 1024 x 768 Max. color : 16.7M Luminance : 800 nit View Angel : 170° (H), 170° (V) Contrast Ratio : 900 : 1 LED backlight lifecycle: 50,000hrs
Signal Input	VGA + HDMI + AV (BNC) + Audio + USB
OSD	Auto; Menu; Left; Right; Exit/Select; Power On/Off

Touch Screen	Internal USB interface controller - Projected Capacitive Multi Touch (10 points) Light transmission: 85% or more Surface hardness : 6H Operation system : DOS; Windows XP / 7 / 8.1 / 10 / 11; Linux
Power Supply	Input: 12-24VDC Wide-range AC power to DC Adapter: 100-240VAC, 50/60Hz to DC12V/2A
Construction	Heavy-duty steel chassis
Environment	Operating temperature: --20 °C to 60 °C Storage temperature: -30 °C to 70 °C) Storage humidity: 10% to 95%, non-condensing Vibration: 50 to 500HZ 1G PTP Shock: 10G /peak( 11m sec)
Safety	CE/FCC/Rohs
Dimension W x H x D ( mm )	285 x 224 x 34 mm
Ordering Information	
SLR-121T	12.1" Sunlight Readable Industrial Display with PCT Touch

