

**Model: SS-400R8P (400watt + 400watt)
400W Mini Redundant Power Supply for 4U chassis**



Features

- PS/2 Size design.
- Hot-Swappable & Power Sharing capability.
- Full Range AC Input.
- Efficiency: $\geq 73\%$ at full load. (Normal Line)
- Active PFC.
- Hold-Up Time: 16ms at maximum load & normal input voltage.
- OVER VOLTAGE PROTECTION.
- SHORT CIRCUIT PROTECTION.
- OVER POWER PROTECTION.
- NO LOAD OPERATION.
- ENVIRONMENT TEMPERATURE
 - Operation Temperature: 0°C to 50°C
 - Cooling: By forced air
 - Storage Temperature: -20°C to 70°C
 - Humidity: 5 to 90% non-condensing.
- RELIABILITY
 - MTBF OF POWER SUPPLY ELECTRONIS
 - 80,000 hours at full load and 25°C ambient temperature
 - LIFE EXPECTANCY OF FAN 40,000 hours at 40°C
- Dimension (L x W x H): 200 X 150 X 86 mm / 7.87 x 5.9 x 3.38 (inches)







AC Input

- Input voltage: 90 ~ 264VAC Full-Range.
- Frequency: 50 - 60 Hz.
- Input Current: 8A for 115VAC, 4A for 230VAC.
- Inrush Current: 60A for 115VAC, 80A for 230VAC.

DC Output

Output Voltage	+5V DC	+12V DC	+3.3V DC	-12V DC	+5VSB
Output Current(Max)	25A	28A	25A	0.8A	2A
Output Current(Min.)	3A	2A	1A	0.1A	0.1A
Ripple/Noise Max.(P-P):	50mv	120mv	50mv	150mv	50mV
Line Regulation:	±1%	±1%	±1%	±1%	±1%
Load Regulation:	±5%	±5%	±5%	±10%	±5%

Connectors

Output Connector						
Quantity	(20+4)P x1	M8P x1	M4P x1	HDD x 7	Floppy x 1	LED

Mechanical Drawing

