

Model: SSD1628-VGA
16.3" Stretch Digital Display



Main Feature

- 16.3" Resizing LCD, 500 nits LED backlight, 1366x238
- VGA + HDMI Input
- Resizing display (aspect ratio of 16:2.8)
- Brightness of 500 nits
- Resolutions: 1366 x 238
- Low power consumption
- Backlight MTBF: 70,000 hours

Specification	
Product Model	SSD1628-VGA
LCD Panel	Display Type : 16.3" Resizing LED Panel LCD Resolution : 1366 x 238 Luminance : 500 nit Contrast: 1,000:1 View Angel : 170° (H), 160° (V)
Signal Input	VGA + HDMI
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
Touch Screen (optional)	Internal USB interface controller - Projected Capacitive Multi Touch (10 points) Light transmission: 85% or more Surface hardness : 6H Operation system: Windows XP / 7 / 10 / 11; Linux
Power Supply	DC12V@ 5A, External AC adapter (110-240VAC Wide range input)
Construction	Heavy duty steel

Environment	Operating temperature: 32 °F-113 °F (0 °C to 45 °C) Storage temperature: -4 °F-140 °F (-20 °C to 60 °C) Storage humidity: 10% to 95%@ 40°C , on-condensing Vibration: 10 ~ 150Hz, 0.15mm 10 cycles 1G Shock: 30G peak acceleration (11 msec. duration)
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	Dimensions: 435 x 100 x 44mm
Weight	NET weight: 2KG Gross weight: 3KG

Ordering Information

SSD1628-VGA	16.3" Stretch Digital Display
-------------	-------------------------------

Structure Diagram Unit :mm

